

10", 12", 14", 20" SAW ARM ASSEMBLIES



**ENGINEER YOUR OWN SYSTEM!
MOUNT TO YOUR ASSEMBLY!
AVAILABLE AS:
ABRASIVE, NON-FERROUS, DRY CUT
MANUAL OR SEMI-AUTOMATIC!**



KM20AS



KM20AS 16,18,20" arm assy., 15 HP, 3 PH (220/440 60 hz), Less switch, single 4 bolt trunnion mount, 1" arbor, 1/2 round guard, abrasive only, Spindle RPM 2500, Less wheels, Please specify voltage, Weight: 500 lbs.

K20AS



K20AS 16,18,20" arm assy., abrasive or non-ferrous blades. 15 HP, 3 PH (220/440 volt 60 hz), 1" arbor, Spindle RPM 2500, dual trunnion mount, less wheels/blades, less switch, Please specify voltage, Weight: 500 lbs.

HS14AS
12" - 14" blade



HS14AS 12-14" blade, Non-ferrous arm assy., 5 HP, 1 PH (220 volt 60hz), 3 PH (220/440 60 hz), OSHA guard for carbide blades, 1" arbor, Spindle RPM 4400, 4 bolt mount, Manual switch, Please specify voltage, Weight: 240 lbs.

HS14ASPH



HS14ASPH 12-14" blade, Non-ferrous arm assy., 5 HP, 1PH 220V, 5HP, 3PH (220/440) semi-automatic, air/oil down feed, OSHA guard for carbide tipped blades, 1" arbor, Spindle RPM 4400, 4 bolt mount, Manual switch, Please specify voltage, Weight: 250 lbs.

K10AS (Not shown), 10" arm assy., abrasive wheel only, 3 HP, 1PH(110/220 volt), 3 HP (220/440), manual switch, 5/8" arbor, spindle RPM 3450, 4 bolt mounting, Less wheel, Please specify voltage, Weight: 84 lbs.

K12-14AS (Not Shown), 12-14" arm assy., abrasive wheel only, 5 HP, 1 PH (220 volt 60 hz), 3 PH. (220/440 volt 60 hz.), manual switch, 1" arbor, Spindle RPM 4400, 4 bolt mounting, less wheel, Please specify voltage, Weight: 178 lbs.

HS14ASDC (Not Shown), 12-14" blade, 5 HP, 1 PH(220 volt 60 hz) 3 PH (220/440 volt 60 hz), Dry cut carbide blade for 1/4" wall angle, tubing, structural, Spindle RPM 1300., 1" arbor, 4 bolt mount, Manual switch, less blade. Please specify voltage, Weight: 240 lbs.

ABRASIVE MITERING SAWS



MODEL KM20-22V-15

- 20" or 22" wheel.
- 1" spindle, 2500 RPM.
- Dual air chain vises.
- Capacities: Straight 4" solid, 6" most shapes;
- 3" solid, 5" most shapes at 45°.
- Covered hood with vacuum base.
- Dimensions — L 52" x W 63" x H 68".
- Mitres 45° left or right.

MODEL KM20-22V-15 15 HP saw duty, 3 phase (220/440V). Magnetic starter. Air-operated chain vise standard. Uses 20" abrasive wheel (not included). 1" wheel arbor. Built-in dust collector in base with hood, dust bag, 1200 CFM. Wt. 1700 lbs.

MODEL KM20-22V-20 Same as above, with 20 HP motor, 3 phase (220/440V); please specify voltage.