

BELT SANDERS

- 4" x 60" belt.
- 1 HP, 1 PH or 3 PH.
- Direct drive.
- 3450 RPM — 4" pulley.
- Platen — reversible 4" x 17"
- Table — Cast iron 4" x 6".
- 3600 SFPM.
- Full OSHA guard.
- Easy tracking.
- Quick belt change.
- Horizontal model available.
- Vacuum base 400 CFM.
- Dimensions — L 18" x W 26" x H 60".

MODEL S460V



MODEL S460D

- 4" x 60" belt.
- Direct drive.
- Reversible platen 4" x 17".
- Table — 4" x 6".
- Full OSHA guard.
- Easy tracking.
- Quick belt change.
- Dimensions — L 14" x W 16" x H 33".

MODEL S460D 1 HP, 1 PH or 3 PH. Please specify voltage and phase. Manual switch. Wt. 145 lbs.



HEAVY-DUTY!

MODEL S460V 1 HP, 1 PH or 3 PH, manual switch, please specify phase and voltage. DCV-6 vacuum base. Wt. 485 lbs.

MODEL S4SWB



- 4" x 36" wet benchtop.
- Pre-set belt tension.
- Quick change belt.
- Internal pump.
- Platen 4" x 6".
- Dimensions — L 20" x W 20" x H 12".
- Good for met labs.

MODEL S4SWB 4" x 36" wet, 1/2 HP, 1 PH TEFC. Wt. 110 lbs.

MODEL S4SWBD 4" x 36" wet, belt and 8" disc. 1/2 HP, 1PH TEFC. Wt. 130 lbs.

RUGGED!



MODEL S460W

- Heavy stand.
- Magnetic switch, low-voltage 24 volts at switch.
- Spindle RPM — 2800.
- Flood coolant, 10 gal., 1/3 HP, 20 GPM.
- Platen — 4" x 17".
- Work table — 4" x 6".
- Dimensions — L 36" x W 24" x H 63".
- Available vertical or horizontal (specify when ordering).

MODEL S460W 4" x 60" wet belt sander. 3 HP, 1 PH or 3 PH, saw duty motor. Please specify voltage. Coolant pump and tank with splash guards. Magnetic switch. Wt. 485 lbs.