

TWO 23 SPINDLE DRILL HEADS WITH STEEL GEARS

# 2-46 Line Boring Machine

- ▶ **MANUFACTURED IN THE USA**
- ▶ **Ideal for fast drilling of boards and slots**
- ▶ **Versatile for quick changes on a production program**
- ▶ **5½" to 27" distance between drill heads**
- ▶ **Head movement by digital measure**
- ▶ **Powder Coated Fabricated Surfaces**
- ▶ **Telemechanique Control System**
- ▶ **Powered by 2 BALDOR motors**

**NOW  
WITH  
THROUGH  
BRAKE**

## features & specifications

- Two 23 spindle drill heads with steel gears.
- Two Air clamping cylinders.
- Position Indicator.
- 3048mm (120") maximum fence length.
- Air index pins.
- Working Table Height = 37.5"
- Pneumatic Pedal Control
- Center distance between spindles = 32mm
- Center distance between first & last drill spindles = 704mm (27.7")
- Drill spindle accepts 10mm shank bits.
- Motors (2) = 2HP - 208-230/450V [6.2-5.8/2.9 Amps] 60 cycle - Three Phase
- Spindle Speed = 3450 rpm
- Maximum drilling depth = 6.03mm (2-3/8")
- Operating pressure = 80-100 psi
- 42" x 50" floor space required (120" x 55" w/extensions)
- Machine weight (approx.) = 1,000 pounds

**One Year Warranty on workmanship and manufacturing**

Conquest Industries, Inc. Reserves the right to alter and/or modify the products shown without prior notice. ©Copyright 1999 Conquest Industries, Inc. No portion of this publication may be reproduced in whole or in part without the written consent of Conquest Industries, Inc.

9915 BELL RANCH DRIVE • SANTA FE SPRINGS, CALIFORNIA 90670  
TEL: 800-368-2278 FAX: 562-906-1112 E-MAIL: sales@conquestind.com

**CONQUEST** INDUSTRIES 