

THAYER

- NEW MACHINERY
- USED MACHINERY
- TOOLING

**Since
1946**

**email: machinery@wwth:
www.thayeru**

**1444 F
Pacif**

DISTRIBUTOR OF PROFIT PRODUCING WOODWORKING MACHINERY AND

**TOLL FREE (800) 323-7430
(636) 257-3311**



Mereen Johnson 312-DC-SR1R Selective Gang Rip Saw

Machine: Selective Gang Rip Saw

Brand: Mereen Johnson

Model Number: 312-DC-SR1R

Year of Manufacture: 2007

- Mereen Johnson 312-DC-SR1R Selective Gang Rip Saw
- Select Saw and Horizontal Adjust: (1) Independently adjustable inboard select saw assembly with traveling shoe hold dc adjustment at nominal 4" per second. 1" Minimum distance between adjustable saw and outboard fixed saw. Set up for mounted saw blades. Arranged for addition of second inboard select saw assembly. Arranged for integration to Rip Opti be specified)
- Capacities: 12" Arbor capacity, 3" thickness capacity with 14" Diameter saw blade, 22" minimum part length and a 6" thr
- 50 HP, 3600 RPM, TEFC MJ direct drive arbor motor
- 3 HP TEFC Feed motor; 30' to 150' per minute feed rate; frequency inverter speed control
- 12" Long x 2-9/16" Diameter arbor with 1/2" wide x 1/8" double key - 180° opposed; arranged for Camlock collars
- Laser Guide Lights: (1) Diode laser mounted to shifting saw mechanism. Includes (2) Diode laser machine mounted - 12 pivoting, extruded aluminum laser bracket arranged for mounting up to (4) diode laser lights with manual horizontal adju
- Color touchscreen interface mounted in freestanding control pedestal with 20' SO cord

- Feed bed is 5" pitch Double Vee chain, dip bed, Dual-Life contoured dip cams, aluminum feed slats and steel-backed rubber lube with low level auto shut-off
- Pressure head includes (4) 3" diameter air loaded overhead idle press rolls. Pressure head with hinged access plate top machine. Access plate with hold up device, electric interlock and air cylinder lock out. Arranged for (2) spring loaded trays 1-1/8" Minimum between Camlock mounted saw blades using moving shoe hold downs
- Single bottom and double upper infeed and single upper outfeed Anti-Kickback Assemblies
- Includes (2) upper dust hoods: (1) 10" diameter at outfeed and (1) 5" diameter at anti-kickback. (1) Lower 5" diameter at
- Includes used tooling: Sawblades and (2) Camlock Collars

FOB Pacific, MO

Machine specifications are based on original manufacturer's information and are subject to verification. Equipment is subject to prior sale without notice. Prices quoted do not include any sales or use tax. Carting of used machinery is not included.